



COMMERCIAL PRESSURE GAUGE

Dial Size: 250 / 150 / 100 / 80 / 63 / 50 / 40 mm

Range: Vacuum, Compound, 0....1 Kg/cm² to 0....1500 Kg/cm²

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type / Helix Type

Case & Bezel: Drawn Steel Black Coated

Movement: Brass

Bourdon: Brass

Socket: Brass

Connection: 1/8", 1/4", 3/8". 1/2" BSP/NPT (M/F)

Mounting: Bottom / Back direct, Bottom Surface, Back Panel, Back Bracket

Mounting

Pointer: Aluminum, Black

Dial: Aluminum, Black numerals in White background

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Joint: Soldering

Glass: Plain Glass, Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.6, Class 2.0

Operation Temperature: -40~80 °C

Enclosure Protection: IP-55, IP-65 (filled)



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com