



COMPACT SEALED PRESSURE GAUGE

Dial Size: 63 mm

Range: up to 21 Kg/cm²

Configuration: Compact Sealed

Shape of Bourdon: 'C' Type

Case & Bezel: SS 304

Movement: SS 304

Diaphragm: SS 316L

Bourdon: SS 316

Socket: SS 304 / SS 316

Pointer: Aluminum, Black (Micro- zero Adjustment, Optional)

Dial: Aluminum, Black numerals in White background

Threaded Connections: 1/4" BSP/NPT (M/F)

Mounting: Bottom / Back Direct

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Blow out Disc: Neoprene, at back side of case.

Joint: Argon / TIG Welding

Glass: Safety Glass, Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.6 acc. EN 837-3

Sealing Fluid: Silicon Oil

Enclosure Protection: IP-55, IP-65 (filled)

Standard: IS 3624 / EN 837-3

Service indented : Gaseous & Liquid Media, Low viscosity media



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com