

ELECTRIC CONTACT PRESSURE GAUGE

Dial Size: 100 / 150 mm

Range: Vacuum, Compound, 0....1 Kg/cm² to 0....1500 Kg/cm²

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type / Helix Type

Case & Bezel: SS304

Movement: SS 304

Bourdon: SS 316

Socket: SS 304 / SS 316

Pointer: Aluminum, Black

Dial: Aluminum, Black numerals in White background

Connection: 1/4", 3/8", 1/2" BSP/NPT (M/F)

Contact: Single / Double / Triple Contacts

(NO, NC, 2NO, 2NC, NO-NC, NC-NO, 3NO, 3NC, 2NO-NC, 2NC-NO)

Contact Ratings: 380 V AC, 1A, 30W

Relay Ratings: 220 V DC, 10 A (optional)

Mounting: Bottom / Back Direct, Bottom Surface, Back Panel, Back Bracket Mounting

Joint: Argon / TIG Welding

Glass: Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.0 % acc., Class 1.6 % acc.



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com