

ELECTRIC CONTACT TEMPERATURE GAUGE

TYPE: LIQUID FILLED THERMOMETER WITH CONTACTS

Dial Size: 250 / 150 / 100 mm

Range: -40 °C... up to 600 °C

Case & Bezel: SS304

Stem : SS 304 / SS 316

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type

Movement: SS 304

Bourdon: SS 316

Capillary: SS 316, Armor Capillary SS 304 (Optional), PVC Coating (Optional)

Pointer: Aluminum, Black (zero Adjustment, Optional)

Dial: Aluminum, Black numerals in White background

Connection: 1/4", 3/8", 1/2" BSP/NPT (M/F)

Contact : Single / Double / Triple Contact, 380 V AC, 1A, 30W

Relay : 220 V DC, 10 A (optional), Coil capacity: 24V DC

Mounting: Bottom / Back Direct, Bottom Surface, Back Panel, Back Bracket Mounting

Joint : Argon / TIG Welding

Window: Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.6 acc.

Enclosure Protection: IP-55, IP-65



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com