

# **HOMOGENIZER PRESSURE GAUGE**

Dial Size: 100 / 150 mm

Range: 0....1500 Kg/cm<sup>2</sup>

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type / Helix Type

Case & Bezel: SS304

Movement: SS 304

Bourdon: SS 316

Socket: SS 304 / SS 316

Pointer: Aluminum, Black

Gasket : Nitric ( Food Grade )

Dial: Aluminum, Black numerals in White background

Diaphragm : SS 316 L

Capillary: SS 316, Armor Capillary SS 304 (Optional)

Mounting: Direct Mount, Square Clamp Mount, Tung type SMS Connection

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Blow out Disc: Neoprene, at back side of case

Joint: Argon / TIG Welding

Glass: Acrylic Glass

Over-range Protection: 30% above FSD

Accuracy: 1.6% FSD EN 837-3

Enclosure Protection: IP-55, IP-65 EN 837-3

Standard: IS 3624 / EN 837



## **BRINDA INDUSTRIES**

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: [info@lapressuregauges.com](mailto:info@lapressuregauges.com)