



INDUSTRIAL PRESSURE GAUGE

Dial Size: 300 / 250 / 150 / 100 / 80 / 63 / 50 / 40 mm

Range: Vacuum, Compound, 0....1 Kg/cm² to 0....2100 Kg/cm²

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type / Helix Type

Case & Bezel: SS304 / Aluminum

Movement: SS 304

Bourdon: SS 316

Socket: SS 304 / SS 316

Pointer: Aluminum, Black (Micro- zero Adjustment, Optional)

Dial: Aluminum, Black numerals in White background

Connection: 1/8", 1/4", 3/8", 1/2" BSP/NPT (M/F)

Mounting: Bottom / Back Direct, Bottom Surface, Back Panel, Back Bracket Mounting

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Joint: Argon / TIG Welding

Glass: Safety Glass, Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.0, Class 1.6 acc. EN 837-3

Operation Temperature: -40~200 °C

Enclosure Protection: IP-55, IP-65 (filled)

Standard: IS 3624 / EN 837



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com