

# LIQUID FILLED TEMPERATURE GAUGE

---

Dial Size: 250 / 150 / 100 mm

Range: -40 °C... up to 600 °C

Case & Bezel: SS304

Stem : SS 304 / SS 316

Configuration: Bourdon Tube

Shape of Bourdon: 'C' Type

Movement: SS 304

Bourdon: SS 316

Capillary: SS 316, Armor Capillary SS 304 (Optional), PVC coating (Optional)

Pointer: Aluminum, Black (zero Adjustment, Optional)

Dial: Aluminum, Black numerals in White background

Connection: 1/4", 3/8", 1/2" BSP/NPT (M/F)

Mounting: Bottom / Back Direct, Bottom Surface, Back Panel, Back Bracket Mounting

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Joint : Argon / TIG Welding

Glass: Safety Glass, Acrylic Glass

Over-range Protection: 30% above FSD

Accuracy: Class 1.0 acc., Class 1.6 acc.

Enclosure Protection: IP-55, IP-65



---

## BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: [info@lapressuregauges.com](mailto:info@lapressuregauges.com)