



MUD PRESSURE GAUGE

TYPE: FIXED DIAL ROTATING DIAL / ROTATING DIAL FIXED POINTER

Dial Size: 100 / 115 / 150 mm

Range: 0-10 Kg/cm²...up to 6000 PSI

Configuration: Diaphragm

Shape of Bourdon: Helix Type

Case & Bezel: SS304

Movement: SS 304

Bourdon: SS 316

Socket: SS 304 / SS 316

Pointer: Aluminum, Black

Gasket : Nitric (Food Grade)

Dial: Aluminum, Black numerals in White background

Seal Flange : SS 316

Diaphragm : SS 316 L Tig Welded Bright Finish

Mounting: Direct Bottom

Connection : 1" & 2" BSP / NPT (As Per Requirement)

Dampening Liquid: Glycerin with leak proofing and Weather Proof both Available

Joint: Argon / TIG Welding

Glass: Acrylic Glass

Over-range Protection: 30% above FSD

Accuracy: Class 1.0 % acc.(1.6% FSD for filled gauges), EN 837-3

Enclosure Protection: IP-65



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com