

SCHAFFER DIAPHRAGM PRESSURE GAUGE

Dial Size: 150 / 100 mm

Range:

Low Range : up to 200 mmWC (Positive / Negative), Vacuum

High Range : up to 21 Kg/cm²

Configuration: Schaffer Diaphragm

Case & Bezel: SS 304

Movement: SS 304

Diaphragm: SS 316L

Socket: SS 304 / SS 316

Pointer: Aluminum, Black (Micro- zero Adjustment, Optional)

Dial: Aluminum, Black numerals in White background

Threaded Connections: 1/4", 3/8", 1/2" BSP/NPT (M/F)

Top Chamber: SS 304

Bottom Chamber: SS 304

Mounting: Bottom / Back Direct

Blow out Disc: Neoprene, at back side of case

Joint: Argon / TIG Welding

Glass: Safety Glass, Acrylic

Over-range Protection: 30% above FSD

Accuracy: Class 1.6 acc. EN 837-3

Enclosure Protection: IP-55, IP-65

Standard: IS 3624 / EN 837

Service indented: Gaseous & Liquid Media, Low viscosity media



BRINDA INDUSTRIES

C-1/1301, GIDC CHHATRAL, NORTH GUJARAT, INDIA

PH-91 2764 233434 FAX-91 2764 233087

<http://lapressuregauges.com>

To Order Mail Us: info@lapressuregauges.com